

What is claimed is:

1. A versatile counting-meter, comprising a main body  
in the form of a casing, said casing being provided  
5 at a front surface with at least a liquid crystal  
display (LCD) screen, a key for sensor switching,  
a key for operating, and an ON/OFF button, and in  
an internal space thereof with an electronic circuit  
for a microprocessor, a swing-link counting means  
10 for implementing a pedometer function, and two  
laterally spaced metal bars having free ends exposed  
from a rear surface of said casing to serve as two  
electrically conductive contacts; said counting-  
meter being characterized in that said casing is  
15 provided at said rear surface with a connecting  
means including two laterally and symmetrically  
spaced parallel rails and a clip, said clip being  
an elastic plate providing sufficient elastic  
restoring force and screwed at an upper end to an  
20 upper part of said rear surface of said casing  
between two upper ends of said two rails, such that  
a lower free end of said clip is located in a recess  
provided on said rear surface between two lower ends  
of said two rails; and said lower free end of said  
25 clip being elastically outward turnable for firmly  
clamping said casing to a user's belt due to said  
elastic restoring force provided by said clip.

2. The versatile counting-meter as claimed in claim 1,  
wherein said lower free end of said clip is normally  
pulled by said elastic restoring force of said clip  
5 inward to flatly locate in said recess on said rear  
surface of said casing.

3. The versatile counting-meter as claimed in claim 1,  
wherein said lower free end of said clip is provided  
10 at a predetermined position with a hole, and said  
recess on said rear surface of said casing being  
provided with a raised retaining socket  
corresponding to said hole on said clip so as to  
project from said hole when said clip is flatly  
15 located in said recess.